



Product | ekoa® Surface: Natural

1. Product Description

ekoa® Clean-Air Certified, high-performance surfaces are crafted with natural fibers and plant resins for durable, elegant, and truly sustainable finishes with a luxury look and feel.

2. Technical Specifications

Total Weight: 716 GSM / 21.1 OZ/Yd²

Thickness: 0.69 mm / 0.027"

Width: 1.23m / 48.5"

Backing: Paper

Composition: See HPD

Tensile strength: W102 Type III

Tear Strength: W102 Type II

Fire: ASTM E-84 Class B

Flame Spread: 65

Smoke Development: 10

VOC: Clean Air Gold Certified

3. Storage & Handling

Store in a cool, dry place to prevent warping and cracking.

Handle with care to prevent damage to the thin sheets of ekoa® material.

Avoid exposure to moisture or extreme temperature fluctuations.

Store without sharp bends or corners to prevent fractures.

4. Cleanability

Water based cleaners, mild soap, or 10:1 bleach to effectively clean ekoa® of smudges and stains. Do not use harsh solvents such as acetone.

5. Glueing

For wallcovering applications use clay based wallcovering adhesives such as:
PRO-774 CLAY STRIPPABLE WALLCOVERING ADHESIVE

For panelized products use wood glues such as:
TITEBOND II PREMIUM WOOD GLUE



Perform compatibility testing with other adhesives prior to use.

6. Safety Information

ekoa® material is non-toxic and does not pose a health risk when handled properly. Always follow manufacturer's instructions and safety guidelines when using adhesives or finishing products. See MSDS for more details.
